Appl. No. 10/593,599 Amendment dated April 23, 2009 Reply to Office Action dated January 23, 2009

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently amended) A method of for marine seismic data acquisition,

comprising:

obtaining a 3D wavefield by cross-line acquisition using one or more marine seismic

sources and a plurality of marine seismic receivers arranged into one or more lines, wherein:

the one or more marine seismic sources are towed behind a seismic vessel;

Docket No.: 57.0619 US PCT

and

an offset between shooting locations of the one or more seismic sources is

regarded as an equal shift of the line of seismic receivers; and

decomposing a the obtained seismic wavefield, wherein a 3D wavefield is obtained

by a cross-line acquisition and filtered by applying a decomposition filter having two spatial

directions to obtain a decomposed wavefield.

2. (Currently amended) The method of claim 1 wherein the decomposition is

for at least one of a group consisting of up- for down going decomposition, P/S decomposition,

elastic decomposition and acoustic decomposition.

3. (Currently amended) The method of claim 1 wherein the filter comprises

in-line component (k_x) and cross-line components component (k_y) or a spatial representation of

the in-line <u>component</u> (k_x) and cross-line <u>components</u> <u>component</u> (k_y) .

Page 2 of 7

Appl. No. 10/593,599 Amendment dated April 23, 2009 Reply to Office Action dated January 23, 2009

4.

filter.

(Original) The method of claim 1 wherein the filter is applied as a cascaded

PATENT

Docket No.: 57.0619 US PCT

- 5. (Original) The method of claim 1 wherein the filter is a compact filter.
- 6. (Original) The method of claim 1 wherein the filter filters an obtained pressure wavefield.
- 7. (Original) The method of claim 1 wherein the filter exclusively filters an obtained pressure wavefield.
- 8. (Original) The method of claim 1 wherein the step of applying the filter is preceded by a calibration step to match geophone recordings with hydrophone recordings.
- 9. (Original) The method of claim 1 wherein the step of applying the filter is followed by a step of removing multiples from a component of the decomposed wavefield.
- 10. (Currently amended) The method of claim 1 wherein the step of applying the filter is followed by a step of imaging or migrating the filtered wavefield to generated generate an image of subterranean formations.
- 11. (Original) The method of claim 1 wherein the wavefield is obtained through receivers located on the sea floor.

Appl. No. 10/593,599 Amendment dated April 23, 2009 Reply to Office Action dated January 23, 2009

12. (Original) The method of claim 1 wherein the wavefield is obtained through receivers towed by a vessel.

PATENT

Docket No.: 57.0619 US PCT